

11-2000

7104
PIGMENTS

Harcros Pigments Inc.
11 Executive Dr., Suite 1
Fairview Heights, IL 62208

Product: YELLOW IRON OXIDE
MSDS No. PIGMENT / HPI-018
Revision: Revision 2
Date: November 1995

HAZARD MATERIAL IDENTIFICATION SYSTEM

Health Hazard 0 - Minimal
Flammability Hazard 0 - Minimal
Reactivity Hazard 0 - Minimal
Personal Protection E - Glasses, Gloves, Dust Resp

SECTION I. MATERIAL IDENTIFICATION

Trade/Material Name: YELLOW IRON OXIDE
Description: Yellow Iron Oxide, C.I. Pigment Yellow 42. C.I. No. 77492
Other Designations: Y-0220
YB-2087, YB-2900
YO-2087, YO-2288, YO-2587, YO-2600, YO-2900, YO-3587,
YO-4900, YO-5087, YO-5286, YO-6087, YO-8087,
YLO-1888D, YLO-1988D, YLO-2288D, YLO-3288D, YLO-4088D
YP-1888, YP-2087, YP-2288, YV-1888, YV-1988, YV-2288
YLV-1900, YLV-1950
YS-3487
CAS: 51274-00-1
Chemical Name: Fe₂O₃·H₂O
MANUFACTURER: Harcros Pigments Inc. PHONE: 618-271-4700
11 Executive Dr., Suite 1 E. St. Louis Plant
Fairview Heights, IL 62208

SECTION II. INGREDIENTS AND HAZARDS

<u>INGREDIENT NAME:</u>	<u>CAS NUMBER:</u>	<u>PERCENT</u>	<u>EXPOSURE LIMITS</u>
Iron Oxide Yellow	51274-00-1	>99	ACGIH TLV: 5 mg/M ³ TWA (Iron Oxide Fume as Fe) OSHA STEL: 10 ppm (Iron Oxide Fume as Fe)

(Ingredients and Hazards continued on next page)

SARA TITLE III: Section 313 Supplier Notification

This product does not contain toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

SECTION III.

PHYSICAL/CHEMICAL CHARACTERISTICS

Appearance and Odor: Yellow Powder, No Odor

Solubility in Water (%): Insoluble

Specific Gravity (H₂O=1): 4.03

% Volatile by Volume: 0

SECTION IV.

FIRE AND EXPLOSION DATA

Flash Point (method): Not flammable

Extinguishing Media: Not flammable. Use appropriate extinguishing media for the combustible material involved in the fire.

Unusual Fire or Explosion Hazards:

Special Firefighting Procedures: Firefighters should use self-contained breathing apparatus.

SECTION V.

REACTIVITY DATA

Material is stable - Hazardous polymerization will not occur

Chemical incompatibilities: It is incompatible with hydrazine, calcium hypochlorite, performic acid, and bromine pentafluoride.

Conditions to avoid:

Hazardous Decomposition Products:

Summary of Health Risks
and Symptoms of Exposure:

May cause mechanical skin and eye irritation. Repeated and prolonged exposures to iron oxide dust may cause a benign pneumoconiosis called siderosis.

Principal Routes of Entry:

Inhalation, ingestion, skin and eye irritation

Acute Effects:

Causes mechanical skin and eye irritation.

Chronic Health Effects(s):

Prolonged inhalation of iron oxide dust is known to produce a condition known as siderosis. On X-rays it appears to be a benign pneumoconiosis and is not associated with pulmonary fibrosis or disability unless there is concurrent exposure to other fibrosis-producing materials such as silica. The TLV is set to protect against siderosis.

Emergency and First Aid Procedures:

Eye Contact:

Flush eyes with generous amounts of water for at least 15 minutes. Call a physician if irritation persists.

Skin Contact:

Wash skin with mild soap and water.

Inhalation:

Remove to fresh air. Call a physician.

Ingestion:

If conscious, give large quantities of water to induce vomiting. Get medical attention.

SECTION VII.

PRECAUTIONS FOR SAFE HANDLING, USE OR DISPOSAL

Spill / Leak procedures:

Vacuum or use wet clean-up techniques and place waste material in closed container.

Waste management / disposal:

Disposal must be made in accordance with Federal, State and local regulations. Pursuant to 40 CFR part 261 of the Resource Conservation & Recovery Act (RCRA). Regulations currently in effect, discarded Iron Oxide would not be classified as a hazardous waste.

Precautions to be taken
in handling and storing:

For transportation emergencies, call CHEMTREC, 24 hour information service, (800) 424-9300.

Personal protective equipment:

- Goggles: Wear safety glasses or goggles to protect against dust particles.
- Gloves: Leather or rubber gloves.
- Respirator: Use of NIOSH approved dust respirator is recommended when exposure limits may be exceeded.

Workplace Considerations:

- Ventilation: Local exhaust ventilation to collector or containment recommended to control dust to below exposure limits.
- Safety Stations: An eye wash station should be available to the area of use.
- Other: In accordance with good industrial hygiene practice, avoid contact with skin, eyes or clothing. Avoid breathing dust. Keep away from food products. Keep container closed when not in use. Use with adequate, localized ventilation. Wash thoroughly after handling and before eating, drinking or using tobacco products.

SECTION IX.

SPECIAL PRECAUTIONS

DOT Class: Not regulated

Prepared/revised by: R. E. Rader

November 1995

The information presented herein is believed to be accurate and was obtained from sources believed to be reliable. However, the information is provided without any representation or warranty, expressed or implied, with respect to its accuracy or completeness. It is the users' responsibility to determine the suitability of this product and the relevance of this information for their use. Harcor Pigments Inc. does not assume liability resulting from the use, handling, storage, and disposal of this product.