

MATERIAL SAFETY DATA SHEET

Elementis Pigments Inc.
11 Executive Dr., Suite 1
Fairview Heights, IL 62208

Product: UMBERS
MSDS No. PIGMENT / EPI-025
Revision: Original
Date: January 1998

HAZARD MATERIAL IDENTIFICATION SYSTEM

Health Hazard
Flammability Hazard
Reactivity Hazard
Personal Protection

1 - Slight
1 - Slight
0 - Minimal
E - Glasses, Gloves, Dust Resp

SECTION I. MATERIAL IDENTIFICATION

Trade/Material Name: UMBERS
Description: Raw Umbers, Burnt Umbers
Other Designations: RU-9546, BU-1561, BU-5250F, BU-5350F, BU-5452, BU-7052
CAS: 12713-03-0
Chemical Name: Fe₂O₃ + MnO₂ + SiO₂ + H₂O
MANUFACTURER: Elementis Pigments Inc. PHONE: 618-271-4700
11 Executive Dr., Suite 1 E. St. Louis Plant
Fairview Heights, IL 62208

SECTION II. INGREDIENTS AND HAZARDS

<u>INGREDIENT NAME:</u>	<u>CAS NUMBER:</u>	<u>PERCENT</u>	<u>EXPOSURE LIMITS</u>	
Iron Oxide	1332-37-2	45-65	ACGIH TLV: OSHA STEL:	5 mg/M ³ TWA 10 ppm (Iron Oxide Fume as Fe)
Silica - Quartz	14808-60-7	1-4	ACGIH TLV: OSHA PEL:	0.1 mg/M ³ TWA 10 mg/M ³ TWA (Respirable Dust)
Manganese Oxide	1313-13-9	5-15	ACGIH TLV:	5 mg/M ³ TWA (Manganese Dust & Compounds)
Aluminum Oxide	1344-28-1	2-12	ACGIH TLV:	10 mg/M ³ TWA (Compound as Al)

(Ingredients and Hazards continued on next page)

(Ingredients and Hazards continued from previous page)

SARA TITLE III: Section 313 Supplier Notification

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372:

Manganese Compound 5-15% CAS# 1313-13-9

This information must be included in all MSDSs that are copied and distributed for this material.

SECTION III. PHYSICAL/CHEMICAL CHARACTERISTICS

Appearance and Odor: Brown to Dark Brown Powder, no odor
Solubility in Water (%): Insoluble
Specific Gravity (H₂O=1): 3.1-3.8

SECTION IV. FIRE AND EXPLOSION DATA

Flash Point (method): If exposed to open flame, umber will smolder.
Limits: LEL %: N/A UEL %: N/A

Extinguishing Media: As appropriate for surrounding combustibles. When exposed to an open flame, umber will support oxidation, generating heat. Uumber will not self-ignite, however.

Unusual Fire or Explosion Hazards:

Special Firefighting Procedures: Firefighters should wear self-contained breathing apparatus.

SECTION V. REACTIVITY DATA

Material is stable - Hazardous polymerization will not occur

Chemical incompatibilities: MnO₂ is a powerful oxidizer. It must not be heated or rubbed against easily oxidizable matter. Should not be combined with flammable materials.

Hazardous Decomposition Products:

SECTION VI.

HEALTH HAZARD DATA

Summary of Health Risks and Symptoms of Exposure:

Skin contact may cause mechanical irritation due to the abrasion. Eye contact will result in no specific effects other than general particulate irritation in the eye. Not absorbed by the body. Excessive exposure above the TLV can give mild pulmonary irritation.

Principal Routes of Entry:

Inhalation, ingestion

Acute Effects:

Inhalation of the dust may cause mechanical irritation to the respiratory tract. Skin and eye contact may cause a mechanical abrasion irritation.

Chronic Health Effects(s):

Long term overexposure to silica causes silicosis, a form of pulmonary fibrosis. Continued exposure to silica can lead to cardiopulmonary impairment.

Emergency and First Aid Procedures:

Eye Contact:

Flush thoroughly with plenty of water for at least 15 minutes. Get medical help if irritation persists.

Skin Contact:

Wash from skin with mild soap and water.

Inhalation:

Remove to fresh air. Get medical help for any breathing difficulty.

Ingestion:

If conscious, give large quantities of water to induce vomiting. Get medical attention.

Crystalline silica which may be present in quantities greater than 0.1% has been reviewed by IARC. IARC found limited evidence for carcinogenicity of crystalline silica in humans and sufficient evidence in experimental animals.

SECTION VII.

PRECAUTIONS FOR SAFE HANDLING, USE OR DISPOSAL

Spill / Leak procedures:

Those involved in clean-up of spills should use respiratory protection for airborne dust. Vacuum or scoop up spilled material for recovery or disposal, avoiding dusting conditions and using good ventilation. Wetting the spill with a water spray may help to keep the airborne dust levels down.

Waste management / disposal:

Refer to any local, State or Federal regulations for specific disposal information. Pursuant to 40 CFR part 261 of the Resource Conservation and Recovery Act (RCRA) regulations currently in effect, discarded Umbers would not be classified as a hazardous waste.

Precautions to be taken in handling and storing:

For transportation emergencies, call CHEMTREC, 24 hour information service, (800) 424-9300.

Manganese compounds are reportable under SARA Title III, Section 313.

SECTION VIII.**SPECIAL PROTECTION INFORMATION**Personal protective equipment:

- Goggles: Safety Glasses with side shields or dust tight goggles.
- Gloves: Leather or rubber gloves.
- Respirator: If exposure limits are exceeded, an appropriate NIOSH approved dust respirator should be used.

Workplace Considerations:

- Ventilation: Provide adequate exhaust ventilation to meet TLV requirements in the dust to workplace. An exhaust filter system may be required to avoid environmental contamination.
- Safety Stations: An eye wash station should be available to the area of use.
- Other: Good industrial hygiene practice requires that employee exposure be maintained below the recommended TLV. This is preferably achieved through the provision of adequate ventilation where necessary. Where dust cannot be controlled in this way, personal respiratory protection should be employed.

SECTION IX.**SPECIAL PRECAUTIONS**

- DOT Class: Not regulated

Prepared/revised by: R. E. Rader

January 1998

The information presented herein is believed to be accurate and was obtained from sources believed to be reliable. However, the information is provided without any representation or warranty, expressed or implied, with respect to its accuracy or completeness. It is the users' responsibility to determine the suitability of this product and the relevance of this information for their use. Elementis Pigments Inc. does not assume liability resulting from the use, handling, storage, and disposal of this product.